TC8000 Series



Accessories Guide

Step 1:Choose a charging method

Cradle options



Single Slot Cradle w/Spare Battery Charger:

CRD-TC8X-2SUCHG-01: Single slot USB Cradle, w/spare battery charging, charges one device and one spare battery.

Allows USB communication to the device with an additional micro-USB cable.

Requires: Power Supply PWRS-14000-148R and Country Specific 3 wire AC Line Cord.

Additional accessories for single slot cradle



25-124330-01R

Micro-USB to USB Cable for single slot cradle



PWRS-14000-148R

Power supply for single slot cradle: 100-240 VAC, 12VDC, 4.16A. **Requires:** Country specific AC grounded line cord.



23844-00-00R

US AC line cord, 7.5 feet long, grounded, three wire for power supplies.

Note: additional cradle configurations are available via a custom product request. In addition, spare cradle cups are available as service spare parts.

Step 1:Choose a charging method

Cradle options



Multi-Slot Cradle options:

CRD-TC8X-5SCHG-01: 5Slot Charge Only Cradle, charges up to five devices.

CRD-TC8X-5SETH-01: 5Slot Ethernet Cradle, charges up to five devices and provides Ethernet communication.

CRD-TC8X-5SC4BC-01: 4Slot Charge Only Cradle with 4Slot Spare Battery Charger, charges up to 4 devices and up to 4 spare batteries on the same cradle.

CRD-TC8X-5SE4BC-01: 4Slot Ethernet Cradle with 4Slot Spare Battery Charger, charges up to 4 devices and up to 4 spare batteries on the same cradle and provides Ethernet communication.

All Cradles Require: Power Supply PWRS-14000-241R, DC Cord 50-16002-029R and Country Specific 3 wire AC Line Cord.

Additional accessories for multi-slot cradles



PWRS-14000-241R

Power supply for 4 slot cradles:90-264 VAC, 12VDC, 9A. **Requires:** DC and country specific AC grounded line cord.



50-16002-029R

DC cable provides power from the power supply to 4 slot charge only and Ethernet cradles



23844-00-00R

US AC line cord, 7.5 feet long, grounded, three wire for power supplies.

Note: additional cradle configurations are available via a custom product request. In addition, spare cradle cups are available as service spare parts.

Step 2:Choose a mounting option for cradles

Mounting accessories for cradles

Note: A mounting bracket (rack/wall or desktop) is required with any cradle configuration.

Rack/Wall Bracket



BRKT-SCRD-SMRK-01

Wall mounting bracket, allows to install any Single Slot or Multi-Slot cradle on a wall or a 19" IT rack. The bracket also allows to install up to four 4Slot Spare Battery Chargers together on a wall or standard 19" IT rack.

Desktop Bracket



BRKT-SCRD-SSDK-01

TC8000 Desk Mounting Bracket for ShareCradle. Allows to install the Single Slot Cradle w/Spare Battery Charger on a flat surface. (i.e. desktop). Note. This part number includes the bracket only, order single slot cradle separately.



BRKT-SCRD-MSDK-01

TC8000 Desk Mounting Bracket for ShareCradle. Allows to install any Multi-Slot cradle on a flat surface. (i.e. desktop). Note. This part number includes the bracket only, order multislot cradle separately.

Step 3:

Choose battery / battery charging accessories

Spare Battery options

6700 mAh Battery



BTRY-TC8X-67MA1-01

PowerPrecision+ Spare Lithium Ion battery, 6700 mAh. Advanced new battery technology, provides a higher level of intelligence (State of Charge and State of Health) to deliver maximum performance.

Spare Battery Charging Options:



SAC-TC8X-4SCHG-01

4-slot battery charger, charges four spare batteries.

Requires: Power supply PWRS-14000-148R and Country Specific 3 wire AC Line Cord.

Accessories for 4-slot battery charger:



PWRS-14000-148R

Power supply for single slot cradle: 100-240 VAC, 12VDC, 4.16A. **Requires:** Country specific AC grounded line cord.



25-85993-01R

2-way DC cable. For running two SAC-TC8X-4SCHG-01 battery chargers off a single PWRS-14000-241R power supply.



23844-00-00R

US AC line cord, 7.5 feet long, grounded, three wire for power supplies.



PWRS-14000-241R

Power supply:90-264 VAC, 12VDC, 9A. It provides power to two spare battery chargers SAC-TC8X-4SCHG-01 while using a 2-way DC cable. **Requires:** DC and country specific AC grounded line cord.

Step 4:Choose cables/adapters

Cable / Adapter options

USB/Charging Cable



CBL-TC8X-USBCHG-01

Provides USB communication to the device.

Requires: For AC charging, power supply
PWRS-14000-249R and country specific ungrounded AC line cord.

Audio Cables



CBL-TC8X-AUDQD-01

Audio adapter cable, compatible with quickdisconnect wired headsets, for voicedirected picking and PTT applications. Requires: QD headset.



CBL-TC8X-AUDBJ-01

Audio adapter cable, compatible with 3.5mm wired headsets, recommended for PTT applications only.

Requires: 3.5mm headset.



PWRS-14000-249R

Power Supply: 100-240VAC, 5.4 VDC, 3A. Provides charge to the device through a USB/Charging Cable.

Requires: Country-specific ungrounded AC line cord.



RCH51

Rugged wired headset with quick-disconnect



HDST-35MM-PTVP-01

Over the ear headset with/MIC and PTT-3.5mm



50-16000-182R

US AC line cord, ungrounded, two-wire for power supplies PWRS-14000-249R.

Step 5:Choose carrying accessories

Carrying options

Quick-draw Holster



SG-TC8X-QDHLST-01

Soft material holster, side loop accommodates a full sized stylus (SG-TC7X-STYLUS-03).

Requires: Universal belt.

Presentation Holster



SG-TC8X-PMHLST-01

Soft material holster, side loop accommodates a full sized stylus (SG-TC7X-STYLUS-03). Allows to use the device with a wired headset and enables to use the device on free-hand scanning mode.

OR

Requires: Universal shoulder strap or universal belt.



Belt for holster 11-08062-02R

Universal belt for fabric holster.



Shoulder strap WA6010

Universal shoulder strap for fabric holster.



Belt for holster 11-08062-02R

Universal belt for fabric holster.

Step 6:Choose other accessories

Additional accessories







