

OUR Customers

With the great development and excellent marketing team, SPRT has sold its products all over the world, including Southeast Asia, Europe, South American, Middle East and Africa. It has cooperated with over 1000 companies with an annual sales of over 700000 units. For more than a decade, SPRT has always been stepping ahead of the printing industry.

Based on reality and down-to-earth efforts, aiming at international advanced standard, market-oriented as always, SPRT keeps launching high quality products to customers continuously to become the domestic leading and world top-class receipt printer typical enterprise.



POS Receipt Printer

With high quality and perfect sales service, the POS series printers became preferable choice by distributor, reseller and end-users from domestic and overseas market. And they can be found in supermarket, restaurant, hotel, bank and so on.



◆ SP-POS58IV



Features:

- Big gear, Big motor, Big paper roll
- Print head 2 years warranty
- High speed printing
- Easy to use and simple to maintain
- TPH life 60KM



Catering



TAX



POS

Specification



Printing Method	Thermal Line
Resolution	8 dots/mm(203dpi), 384 dots/line
Effective Printing Width	48mm
Printing Speed	70mm/s (25% Print Density) (MAX)
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage
Print Font	GB180230: 24x24; ASCII: 12x24, 9x17
Self-defined Character	Yes
Barcode	1D UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128
	2D PDF417, QR CODE, DATA MATRIX
Interface	RS-232/Parallel/USB/Ethernet/Bluetooth
Cash Drawer Control	DC12V, 1A, 6PIN RJ-11 Socket
Power Supply (Adapter)	DC12V±10%, 2A
TPH	60KM
Paper Type	Thermal Paper
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
Paper Roll Diameter	80mm (MAX)
Paper Supply Method	Drop-in Easy Loading
Paper Cutting Method	Manual
Operating Temp/Humidity	0~50°C /10%~80%
Storage Temp/Humidity	-20~60°C /10%~90%
Dimension	210mmx145mmx126mm(LxWxH)
Weight	898g (NO Paper)

◆ SP-POS58V



Features:

- Auto recognize USB interface
- Versatile and adaptable
- Paper end sensor
- Smart size and easy to use



Retail



Receipt



POS

Specification



Printing Method	Thermal Line
Resolution	8 dots/mm(203dpi), 384 dots/line
Effective Printing Width	48mm
Printing Speed	50mm/s (25% Print Density) (MAX)
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage
Print Font	GB180230: 24x24; ASCII: 12x24, 9x17
Self-defined Character	Yes
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128
Interface	RS-232/USB/USB+ Bluetooth
Power Supply (Adapter)	DC 7.5V±10%, 2A
TPH	50KM
Paper Type	Thermal Paper
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
Paper Roll Diameter	60mm (MAX)
Paper Supply Method	Drop-in Easy Loading
Paper Cutting Method	Manual
Operating Temp/Humidity	0~50°C /10%~80%
Storage Temp/Humidity	-20~60°C /10%~90%
Dimension	150mmx122mmx93.5mm(LxWxH)
Weight	382g (NO Paper)

◆ SP-POS764



Features:

- Auto paper feeding
- Avoid paper jam design
- Multi-interface
- 9 pin bidirectional printing
- Black mark sensor support



Retail



TAX



Garment

Specification



Printing Method	Dot Matrix
Character Per Line	42/35
Printing Speed	76mm Paper Width: 4.4 lps ; 57.5mm Paper Width: 5.6 lps
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage
Print Font	Font A: 7x9; Font B: 9x9 ; Font C:16x16
Self-defined Character	Yes
Interface	RS-2 32/Parallel/USB/Ethernet/USB+ Bluetooth
Cash Drawer Control	DC24V, 1A, 6PIN RJ-11Socket
Power Supply (Adapter)	AC(100-240)V±10%, 50/60Hz, 1.5A
MCBF	7.5 Million Characters
Paper Type	Plain Paper/Pressure-Sensitive Paper
Paper Width	76.5±0.5mm / 57.5mm±0.5mm
Paper Thickness	0.06-0.08mm
Paper Roll Diameter	80mm (MAX)
Paper Supply Method	Drop-in Easy Loading
Auto Cutter	Partial Cut/Full Cut
Paper Cutting Method	Manual or Auto cut
Driver	Windows XP/Windows Vista/Windows 7 /Windows 8/10/ Linux/OPOS
Operating Temp/Humidity	0~50°C /10%~80%
Storage Temp/Humidity	-20~60°C /10%~90%
Dimension	248mmx158mmx140.5mm (LxWxH)

◆ SP-POS88V



Features:

- High speed of printing up to 250mm/s
- Firmware online updating available
- 2D barcode printing support
- Avoid to lose data design



Insurance



Garment



Retail

Specification



Printing Method		Thermal Line
Resolution		8 dots/mm, 576 dots/line
Effective Printing Width		72mm
Printing Speed		250mm/s (25% Print Density)
Character Set		ASCII, GB18030(Chinese), BIG5, Codepage
Print Font		Font A: 12x24; Font B: 9x17
Self-defined Character		Yes
Barcode	1D	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128
	2D	PDF417, QR CODE, DATA MATRIX
Interface		RS-232/Parallel/USB/Ethernet/Bluetooth/WIFI
Cash Drawer Control		DC 24V, 1A, 6PIN RJ-11 Socket
Power Supply (Adapter)		DC24V±10%, 2A
TPH		100KM
Paper Type		Thermal Paper
Paper Width		79.5±0.5mm
Paper Thickness		0.06-0.08mm
Paper Roll Diameter		80mm (MAX)
Auto Cutter		1,000,000 Cuts
Driver		Windows XP/Windows Vista/Windows 7/8/10/ Linux/OPOS
Operating Temp/Humidity		0~50℃ /10%~80%
Storage Temp/Humidity		-20~60℃ /10%~90%
Weight /Dimension		1500g (NO Paper) /200mm×150mm×139mm(LxWxH)

◆ SP-POS88VI



Features:

- Automatic memory printing
- Printing speed setting support
- Anti-electromagnetic interference level 3
- Paper cover and cutter error being detected



Receipt



Catering



Garment

Specification



Printing Method	Thermal Line	
Resolution	8 dots/mm(203 dpi), 576 dots/line	
Effective Printing Width	72mm	
Printing Speed	250mm/s (25% Print Density) (MAX)	
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage	
Print Font	GB18030: 24x24 ASCII: 12x24	
Self-defined Character	Yes	
Barcode	1D	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128
	2D	PDF417, QR CODE, DATA MATRIX
Interface	RS-232/Parallel/USB/Ethernet/Bluetooth/WIFI	
Cash Drawer Control	DC24V, 1A, 6PIN RJ-11Socket	
Power Supply (Adapter)	DC 24V±10%, 2A	
TPH	100KM	
Paper Type	Thermal Paper	
Paper Width /Thickness	79.5±0.5mm /0.06-0.08mm	
Paper Roll Diameter	80mm (MAX)	
Auto Cutter	1,000,000 Cuts	
Operating Temp/Humidity	0~50°C /10%~80%	
Storage Temp/Humidity	-20~60°C /10%~90%	
Dimension	212mm×150mm×135mm(L×W×H)	
Weight	1456g(NO Paper)	

◆ SP-POS890



Features:

- New beautiful appearance
- Improved function and performance
- Firmware online updating available
- Avoid to lose data design



Catering



TAX



Garment

Specification



Printing Method	Thermal Line	
Resolution	8 dots/mm(203 dpi), 576 dots/line	
Effective Printing Width	72mm	
Printing Speed	220mm/s (25% Print Density) (MAX)	
Character Set	ASCII, GB18030(Chinese), BIG5, Codepage	
Print Font	GB18030: 12x24 ASCII: 12x24	
Graph Printing	Diagram, download bitmap supported	
Self-defined Character	Yes	
Barcode	1D	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128
	2D	PDF417, QR CODE, DATA MATRIX
Interface	Serial+USB/ USB+Ethernet	
Cash Drawer Control	DC24V, 1A, 6Pin RJ-11 Socket	
Power Supply (Adapter)	DC 24V±10%, 1.5A	
TPH/Cutter Life	100KM/1,000,000 cuts	
Paper Type	Normal thermal paper 79.5mm×φ80, 57.5mm×φ80	
Paper Thickness	0.06-0.08mm	
Paper Installation	Drop-in Easy Loading	
Paper Cutting Method	Full Cut/ Partial Cut	
Command	ESC/POS	
Dimension	185mm×150mm×123mm(L×W×H)	
Operating Temp/Humidity	0~50°C /10%~80%	
Storage Temp/Humidity	-20~60°C /10%~90%	