



Product Features

- ▲ Intel® Celeron® J4125&Intel® Core i3/i5 Processors
- ▲ True-Flat Projected Capacitive Multi Touch (PCAP)
- ▲ Multi - I/O Interfaces for Peripherals
- ▲ Excellent Ergonomic and Simple Design
- ▲ Modular Peripherals for Easy Installation
- ▲ IP65 for Front Bezel Compliant
- ▲ Aluminum Alloy Die-Casting Housing for Optimal Thermal Dissipation



Main Specification		
Processor	Intel® Celeron® Processor J4125 (4M Cache, up to 2.70 GHz)	Intel® Core™ i3/i5 Haswell Processor
Memory	DDR4 4G 2666 MHz (Max. 16GB)	4GB DDR3L SO-DIMM 1333/1600MHz (Max. 16GB)
Storage	M.2 SSD64GB(Max. 256GB)	M-SATA SSD64GB(Max. 256GB)
Power Supply	12V/5A	12V/5A
OS Support	Win 7/POSReady 7/WE 8.1 Industry/Win 10/Win 11/Linux	Win 7/POSReady 7/WE 8.1 Industry/Win 10 IoT/Linux

Display & Touch		
Display	15.6" FHD LCD Display	15.6" FHD LCD Display
Resolution	1920*1080	1920*1080
Touch	True-flat PCAP touch Screen (Support Multi-touch)	True-flat PCAP touch Screen (Support Multi-touch)

I/O Expansion		
Serial Port	DB9*2	DB9*2
USB Port	USB3.0*2 + USB2.0*4	USB3.0*2 + USB2.0*4
LAN Port	10/100/1000 MB*1	10/100/1000 MB*1
Display Port	VGA*1	VGA*1
Audio	Line-out*1, Mic-in*1	Line-out*1, Mic-in*1
Expansion Slot	Mini-PCIe slot*1	Mini-PCIe slot*1

Physical Dimension		
Packaging Dimension	475mm*295mm*420mm	475mm*295mm*420mm
Gross Weight	5.26KGS	5.26KGS

Environmental		
Operating Condition	0°C - 40°C, 20%RH - 90%RH	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C ~ 70°C, 10%RH - 90%RH	-20°C ~ 70°C, 10%RH - 90%RH

Options&Peripherals		
2nd Display	VFD/10.1" 2nd LCD Display	VFD/10.1" 2nd LCD Display
MSR	Support 1/2/3 track	Support 1/2/3 track
Dallas Key	Dallas I-button Reader	Dallas I-button Reader

I/O Interfaces



ASAP POS