

PPT2-A 2" Thermal Receipt Printer

PPT2-A

- Big motor and big gear design
- High printing speed up to 100mm/s
- Compact and elegant design
- Could fit in 83mm diameter paper roll
- Anti-water splash, anti-dust design, durable in demanding environment
- Provide Windows/Linux driver/OPOS driver
- Printing head reliability: 100KM with 12.5% printing density.
- Multiple interfaces optional
- Support black mark positioning
- Metal mechanism to speed up heat dispersion
- Low power consumption, energy efficient and environment friendly



Specification

Item	Parameter	
Printing	Printing method	Direct thermal printing
	Resolution	203dpi
	Printing width	58mm
	Printing speed	100mm/s
	Printing density	Adjustable from degree 1 to degree 5
Memory	Flash	2MB
Character Set	Font	Font A:12*24, Font B 8*16, CHN:24*24
	Alphanumeric	95
	Expanded character	128*14
	International character	15
Barcode Symbologies	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
Detection	Sensors	Paper out detection
Interface		USB/RS232/Parallel/Ethernet
Power Supply		External power adaptor
	Input	AC 100V-240V, 50-60HZ
	Output	DC 12V-2A



Paper	Paper type	Thermal paper
	Paper width	58mm
	Paper thickness	0.56~0.1mm
	Paper roll diameter	83 mm Max for inner paper feeding,
	Paper loading	Easy loading
Firmware	Emulation	ESC/POS
Software	Driver	Windows 2000/ XP/Vista/7/8/ POSReady/Linux/OPOS
	Working condition	5~45°C , 10~95%RH
Physical Characteristics	Storage condition	-10~50°C /10~95%RH
	Dimension	186 (L) *114 (W) *128(H)mm
	N.W.	1.06kg (without paper roll)
Reliability	TPH	100km

