TP806 3" Thermal Receipt Printer

- Patent design of unique vertical double auto cutter
- High printing speed up to 300mm/s
- Default USB interface and RS232, Parallel,
- Ethernet and WiFi boards optional
- Embedded with 2D barcode edition algorithm which supports the 2D barcode common in the market, such as QRcode/ PDF417
- Provide Windows/Linux driver
- Provide complete OPOS driver
- Support page mode printing
- With paper jam detection and double paper near end detection
- Movable paper guard plate design which supports 58mm, 80mm wide thermal paper
- Waterproof cover optional

Specification

Item		Parameter	
	Printing method	Direct thermal printing	
	Resolution	203dpi	
Printing	Printing width	72mm	
	Printing speed	Max. 300mm/s	
	Printing density	Adjustable from degree 1 to degree 4	
Page Mode		Yes	
Memory	RAM	1Mb	
	Flash	4Mb	
	Font	Font A:12*24, Font B 9*17 CHN:24*24	
Character Set	Alphanumeric	95	
	Expanded character	128*30	
	International character	15	
Graphics		Support bitmap printing with different density	
		and user defined bitmap printing (Max. 64K for	
		per bitmap, and Max. 256K for total)	
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF,	
		CODEBAR, CODE128, CODE93	
	2D	PDF417, QR code(DataMatrix/Maxicode/Azec optional)	
Interface		Default: USB, drawer	
		Optional:RS232, Parallel, Ethernet, WiFi, Bluetooth	
Detection	Sensor	Paper out detection, paper near end detection,	
		paper jam detection, cover open detection	
Power	Input	AC100V-240V 50-60HZ	
Supply	Output	DC 24V±5%, 2.0A, A-1009-3P interface	
Paper	Paper type	Standard thermal paper	
	Paper width	79.5±0.5mm/57.5±0.5mm	
	Paper thickness	0.056~0.1mm	
	Paper roll diameter	Max. 83mm	
	Paper loading	Easy loading	
	Paper cutting	Auto cutting or manual cutting	

TP806





	Operating condition	5~45℃ /10~95%RH
Physical	Storage condition	-10~50°C/10~95%RH
Characteristics	Dimension	145(L)*197(W) *146(H)mm
	N.W.	1.8kg (without paper roll)
	TPH life	150km
Reliability	Cutter life	2,000,000 times
	MCBF	50 million lines
Firmware	Emulation	ESC/POS
Software	Driver	Windows2000/XP/Vista/7/
Solewale	Diriver	8/POSReady,Linux,OPOS

