

Direct thermal Printer

## XP-58IIL



### Key features

- High speed, long lifetime, high quality
- Outstanding functions, Strong stability
- Support main stream OS systems
- Support Chinese Gb2312
- Avoid order missing
- Compatible with ESC/POS commands

### Applications



Shopping



Mart



Restaurant



Hospital





Coffee Shop



Ticketing

# XP-58IIL

## Direct thermal Printer



<b>Model</b>	<b>XP-58IIL</b>
<b>Printing method</b>	Direct thermal
<b>Paper width</b>	57.5±0.5mm
<b>Print width</b>	48 mm
<b>Column capacity</b>	384 dots/line
<b>Printing speed</b>	90mm/s Max.
<b>Interface</b>	USB / USB+Lan / USB+Bluetooth / Parallel
<b>Line spacing</b>	3.75mm (Adjustable by commands)
<b>Fonts Symbology</b>	
<b>Character size</b>	Afont A: 12x24, Font B: 9x17, CHN: 24*24
<b>Characters /Line</b>	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
<b>1D Barcode</b>	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
<b>2D Barcode</b>	QR code (Available with USB+Lan interface)
<b>Input buffer</b>	32 Kbytes / 64 Kbytes
<b>NV Flash</b>	64 Kbytes
<b>Power</b>	
<b>Power adaptor</b>	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A
<b>Power source</b>	DC 12V/2.6A
<b>Cash drawer</b>	DC 12V/1A
<b>Physical characteristics</b>	
<b>Weight</b>	0.561kg
<b>Dimensions</b>	181×130×111.2mm (D×W×H)
<b>Environmental Requirements</b>	
<b>Work environment</b>	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
<b>Storage environment</b>	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
<b>Reliability</b>	
<b>Printer head life</b>	50 KM
<b>Software</b>	
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Windows/Linux/Android/Mac
<b>Utility</b>	Windows & Linux test Utility
<b>SDK</b>	iOS/ Android/ Windows



Scan QR code to checkout Xprinter website for more update information.  
 Phone: (+86 756) 3895 852  
[Http://www.xprintertech.com](http://www.xprintertech.com)  
 Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

