

supoin

SK2202

The SK2202 barcode scanner is a handheld equipment that may read various 1D and 2D symbologies, suitable for RS-232, USB, PS2, virtual USB and other PC interfaces. The development package and drivers are provided for free.

Applicable scope: WeChat, Alipay and other mobile payment services, retail, tobacco, mobile communication, medical, restaurant and tax industry.



Characteristics



Excellent Identification Ability:

Fully supports all commonly 1D, 2D and paper barcodes, quick and accurate scanning.



Sensitive And Responsive Performance :

Manual trigger, continuous scanning with quick and automatic induction system.



Long Service Life :

The button may be operated 30 million times, low power consumption.



High Quality Wires :

Use of high quality wires in the interior along with inflaming retarding materials of international standard, recyclable and practical shell to fully protect the device.



Convenient And Comfortable To Use :

Fashionable and ergonomic design with comfortable handle, convenient for the user during long working hours.

IP54

Industrial Grade :

IP54 industrial grade, solid and light, can bear drops up to a height of 3m on ground impact.

Partners

Microsoft

QUALCOMM

Honeywell

T · · Systems

IN · RAM

swisslog

SK2202 Specifications

Performance Parameter

| | |
|-----------------------|--|
| Image Sensor | CMOS |
| Light source | Visible light (630+10nm) |
| Decoding capabilities | 1D: UPC/EAN with supplemental, Bookland EAN, ISSN, UCC Coupon Extended Code, EAN-13, EAN-8,UPC-A, UPC-E, Codabar, Code 128, GS1-128, Code 39, Code 39 Full ASCII, Code 32, Code 93, Code 11,Matrix 2 of 5, interleaved 2 of 5, Discrete 2 of 5, MSI, Chinese 2 of 5, GSI DataBar Variants, etc. 2D: PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR code, MicroQR, Aztec and special optimized screen payment code. |
| Scanning speed | 350 times/s |
| Angle | ±360°, ±60°, ±60°Roll, Pitch,Skew. |
| Resolution | 4mil and above |
| Printing contrast | Minimum 20% |
| Interface | USB, USB-COM, PS2(optional) and RS232(optional) |

Physical Parameters

| | |
|-------------------|--|
| Overall dimension | LXWXH (110X70X153mm); |
| Weight | 120g |
| Material | ABS+PC (environment-friendly material) |

Environmental Parameters

| | |
|--------------------------|---------------------------------|
| Operating °C | -20° to 55°C |
| Storage °C | -40° to 60°C |
| Luminance of environment | 0 Lux – 100,000 Lux |
| Shock | Falling resistance for 3 meters |
| IP grade | IP54 grade |

Certificates

CCC, RoHS, IP54 grade, CE, FCC and ISO9001



RoHS

Accessories

Optional accessories



The final interpretation of this product is owned by Shenzhen Supoin Technology Corp.

Supoin Technology Corp.

Floor 26, Yinglong Development Center, 6025 Shennan Road,
Futian District, Shenzhen, China

For more information please visit:

www.supoin.net

International hotline:

86-755-82178516

E-mail:

sales@supoin.com



supoin