CHAINWAY



C6000 Mobile Computer

	46		8	651B2						USB Type-c	Google Mobile Service		Ai
Android OS	4G	Wi-Fi	Bluetooth	1D Barcode	2D Barcode	PSAM	NFC	Camera	GNSS	Type-C	GMS	2.0m	AI Engine

Chainway C6000 is our refined and well-built handheld computer while being portable and rugged at the same time. Built with Android 10 / 13 OS and high-performance processor, it features smooth and stable system configuration. It has immensely diverse functionality features for barcode scanning, NFC, and premium features. Meanwhile, with longer battery life, higher performance, and characteristic rugged robustness, Chainway C6000 is the ideal device to be extensively deployed in harsh circumstances like logistics and warehouses. It can assist customers in operation and management levels significantly.











Specification

Physical Characteristics

-				
Dimensions	157.6 x 73.7 x 29 mm / 6.2 x 2.9 x 1.14 in.			
Weight	292 g / 10.3 oz.			
Display	4" TN α-Si 480*800, 16.7M colors			
Touch Panel	Rugged dual touch capacitive touch panel			
	Main battery: Li-ion, removable, 4200mAh			
Power	Standby: over 300 hours			
Power	Continuous use: over 12 hours (depending on user environment)			
	Charging time: 3-4 hours (with standard adaptor and USB cable)			
Expansion Slot	1 slot for Mirco SIM card, 1 slot for MircoSD(TF) or PSAM card (optional)			
Interfaces	USB 2.0, Type-C, OTG			
Sensors	Light sensor, proximity sensor, gravity sensor			
Notification	Sound, LED indicator, vibrator			
Audio	1 microphone; 1 speaker; receiver			
Keypad	3 TP soft keys, 3 side keys, numeric keyboard (Optional : 20 keys)			

Performance

Operating System	Android 10.0 / 13.0; GMS, Soti MobiControl (Only Android 10.0 support); FOTA, SafeUEM supported.				
CPU	Octa-core, 2.0GHz				
RAM+ROM	3GB + 32GB				
Expansion	Supports up to 256GB Micro SD (TF) card				

Communication

	Support 802.11 a/b/g/n/ac/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4,IPV6, 5G PA;					
WLAN	Fast roaming: PMKID caching, 802.11r, OKC					
	Operating Channels: 2.4G(channel 1°13), 5G(channel 36,38,40,42,44,46,48,52,56,60,64,100,104,108,112,116,120, 124,128,132,136,140,149,153,157,161,165, depends on local regulations					
	Security and Encryption: WEP,WPA/WPA2-PSK(TKIP and AES),WAPI- PSK—EAP-TTLS,EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS,PEAP- GTC,etc.					
	2G: GSM850/GSM900/DCS1800/PCS1900					
WWAN	3G: WCDMA: B1/B2/B4/B5/B8 TD-SCDMA: A/F(B34/B39)					
	4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/ B28B/B34/B38/B39/B40/B41					
WWAN (Others)	Depending on the country's ISP					
Bluetooth	V2.1+EDR, 3.0+HS and V4.1+HS, BT5.0					
GNSS	GPS/AGPS, GLONASS, BeiDou, internal antenna					

Developing Environment Chainway Software Development Kit SDK Language Java Eclipse / Android Studio Tool **User Environment** Operating Temp. -4°F to 122°F / -20°C to 50°C -40°F to 158°F / -40°C to 70°C Storage Temp. Humidity 5%RH - 95%RH non condensing Multiple 2 m / 6.56 ft. drops to concrete across the **Drop Specification** operating temperature range Tumble 1000 x 0.5 m / 1.64 ft. falls at room temperature Specification Sealing IP65 per IEC sealing specifications ESD ±15 KV air discharge, ±6 KV conductive discharge **Data Collection** Camera 13 MP Autofocus with Flash Rear Camera **Barcode Scanning (Optional)** 2D Imager Scanner Zebra SE4710; Honeywell N6603 UPC/EAN, Code128, Code39, Code93, Code11, 1D Symbologies Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc. PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, 2D Symbologies MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. NFC (Optional) 13.56 MHz Frequency ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. Protocol Chips M1 card (S50, S70), CPU card, NFC tags, etc.

Accessories (See details in Accessory Guide)



Range

2-4 cm

* Pistol grip is optional, NFC can not coexist with the pistol grip

Notice: Product specifications are subject to change without prior notice. / Model: C6000 / Update Date: 2024-06-28

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

 Address: 9F, Building2, Phase
 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

 Tel: 0086-755-23223310
 Fax: 0086-755-23223310
 Kmail: sales@chainway.on

 Web: http://www.chainway.net