



**27** Keys



**37** Keys



**47** Keys



## C61

### Mobile Computer



Android



4G



Wi-Fi



Bluetooth



1D Barcode



2D Barcode



NFC



UHF



Camera



GPS

Chainway C61 is a new generation rugged handheld computer with robust performance. Built with Android 11/13 OS and Octa-Core processor, it supports 27 keys / 37 keys / 47 keys optional keypad, abundant accessories like trigger handle, and features powerful removable battery. And it delivers optional barcode scanning, RFID, NFC, etc. Additionally, it supports the latest Impinj Gen2X for enhanced RFID performance. This mobile computer can fulfill applications in logistics, warehousing, retail, etc.



# Specification

| Physical Characteristics |                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions               | 202.0 x 72.5 x 32.0mm / 7.95 x 2.85 x 1.26in.<br>( Device Weight for Argentina, Uruguay, Bolivia, Ecuador market: 342~404g, including battery )                                                              |
| Weight                   | 370g / 13.05oz. (SE4710) ; 404g / 14.25oz. (SE4850) / 26 .05oz. / 738g (SE4850, UHF, pistol battery)                                                                                                         |
| Keypad                   | Main keyboard (Optional) : 27 keys / 37 keys / 47 keys;<br>Side keys: 2 scan keys + 2 volume keys + 1 user-defined key                                                                                       |
| Battery                  | 6700 mAh removable main battery, 5200 mAh optional pistol battery, support QC3.0 and RTC; Built in 100mAh backup battery, supporting battery hot swap, improving reliability and ensuring user data security |
|                          | Standby: up to 680 hours (only main battery ; WiFi: up to 560h; 4G: up to 560h)                                                                                                                              |
|                          | Continuous use: over 12 hours (depending on user environment)                                                                                                                                                |
|                          | Charging time: 3.5 hours (charge device by standard adaptor and USB cable)                                                                                                                                   |
| Display                  | 4-inch high definition display, 800*480                                                                                                                                                                      |
| Touch Panel              | Multi-touch panel, gloves and wet hands supported                                                                                                                                                            |
| Sensor                   | Accelerometer sensor, light sensor, proximity sensor, gravity sensor                                                                                                                                         |
| Notification             | Sound, LED indicator, vibrator                                                                                                                                                                               |
| Audio                    | 1 microphone; 2 speakers; receiver                                                                                                                                                                           |
| Card slot                | 1 slot for Micro SIM card, 1 slot for TF card                                                                                                                                                                |
| Interfaces               | USB Type-C, USB 3.1, OTG, extended thimble                                                                                                                                                                   |

| Performance |                                         |
|-------------|-----------------------------------------|
| CPU         | Octa-core, 2.0 GHz                      |
| RAM+ROM     | 3GB + 32GB / 4GB + 64GB                 |
| Expansion   | Supports up to 256GB Micro SD (TF) card |

| Developing Environment |                                                                                                                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating System       | Android 11/13; GMS, 90-day security updates, Android Enterprise Recommended, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported. Committed support for a future upgrade to Android 18 pending feasibility |
| SDK                    | Chainway Software Development Kit                                                                                                                                                                            |
| Language               | Java                                                                                                                                                                                                         |
| Tool                   | Eclipse / Android Studio                                                                                                                                                                                     |

| User Environment     |                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------|
| Operating Temp.      | -4°F to 122°F / -20°C to 50°C                                                                             |
| Storage Temp.        | -40°F to 158°F / -40°C to 70°C                                                                            |
| Humidity             | 5% RH to 95% RH (non condensing)                                                                          |
| Drop Specification   | Multiple 1.8 m / 5.9 ft. drops (at least 20 times) to the concrete across the operating temperature range |
| Tumble Specification | 1000 x 0.5 m / 1.64 ft. falls at room temperature                                                         |
| Sealing              | IP65 per IEC sealing specifications                                                                       |
| ESD                  | ±15 KV air discharge, ±8 KV conductive discharge                                                          |

| Communication |                                                                                                                                                                                |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WLAN          | Support 802.11 a/b/g/n/ac/ax-ready/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6, 5G PA;                                                                                        |
|               | Fast roaming: PMKID caching, 802.11r, OKC                                                                                                                                      |
|               | Operating Channels: 2.4G(channel 1~13), 5G(channel 36,40,44,48,52,56,60,64,100,104,108,112,116,120, 124,128,132,136,140,144,149,153,157,161,165), Depends on local regulations |
|               | Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, WPA3-Enterprise,etc.                                  |
|               |                                                                                                                                                                                |

|                        |                                                          |
|------------------------|----------------------------------------------------------|
| Vo-LTE                 | Support Vo-LTE HD video voice call                       |
| Bluetooth              | Bluetooth 5.1                                            |
| GNSS                   | GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna     |
| WWAN<br>(Europe, Asia) | 2G: 850/900/1800/1900 MHz                                |
|                        | 3G: CDMA EVDO: BC0                                       |
|                        | WCDMA: 850/900/1900/2100 MHz                             |
|                        | TD-SCDMA: A/F(B34/B39)                                   |
| WWAN(America)          | 4G: B1/B3/B5/B7/B8/B20/B38/B39/B40/B41                   |
|                        | 2G: 850/900/1800/1900MHz                                 |
|                        | 3G: 850/900/1900/2100MHz                                 |
|                        | 4G: Android 11: B2/B4/B5/B7/B8/B12/B13/B17/B28A/B28B/B38 |

| Data Collection |                                               |
|-----------------|-----------------------------------------------|
| Camera          |                                               |
| Rear Camera     | Rear 13 MP Autofocus with flash               |
| NFC             |                                               |
| Frequency       | 13.56 MHz                                     |
| Protocol        | ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc. |
| Chips           | M1 card (S50, S70), CPU card, NFC tags, etc.  |
| Range           | 2-4 cm                                        |

| UHF (Optional)     |                                                                                                                               |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Engine             | CM710-1 module based on Impinj E710                                                                                           |
| Frequency          | 865-868 MHz / 920-925 MHz / 902-928 MHz                                                                                       |
| Impinj Gen2X       | Supported                                                                                                                     |
| Protocol           | EPC C1 GEN2 / ISO18000-6C                                                                                                     |
| Antenna            | Circular Polarized Antenna (4 dBi)                                                                                            |
| Power              | 1W (30 dBm, +5 dBm to +30 dBm adjustable)                                                                                     |
|                    | 2W Optional (33 dBm, for Latin America, etc.)                                                                                 |
| Max Read Range     | 27m (Impinj MR6 tag, size70 x 15mm)<br>26m (Impinj M750 tag, size70 x 15mm)<br>30m (Alien H3 Anti-Metal tag, size 130 x 42mm) |
| Fastest Read Rate  | 1300+ tags/sec                                                                                                                |
| Communication Mode | Pin Connector                                                                                                                 |

\* Ranges are measured in the open outdoors and low interference environment, and rate is measured in a laboratory low interference environment, they are affected by tags and environment.

| Barcode Scanning (optional) |                                                                                                                                                                                                             |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2D Scanner                  | Zebra: SE4710/SE5500/SE4750SR/SE4750MR/SE4750DP/SE4850<br>Honeywell: N6603/N6703; CM60                                                                                                                      |
| 1D Symbolologies            | UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.                                                                                      |
| 2D Symbolologies            | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc. |

| Optional accessories(See details in Accessory Guide)          |  |
|---------------------------------------------------------------|--|
| Separate handle with one button, Wrist Strap; Charging Cradle |  |
| Handle + battery (handle battery 5200 mAh, one button)        |  |
| UHF back clip + handle (5200 mAh, one button)                 |  |
|                                                               |  |

Notice: Product specifications are subject to change without prior notice. / Model: C61 / Update Date: 2024-12-04

**CHAINWAY®**

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net