## Label Rewinder Family

## The Rewinder Everyone Can Use

The T10 / T20 rewinder has an idler arm that can be positioned to rewind labels from either side of the printer. Depending on the user's requirements,

the rewinder can rewind "inside or outside" label rolls.



provides rewinder operation status



VR(Speed Adjustment)



## T10 / T20 Label Rewinder Family

Model		т10	т20	
Paper width		4.72" (Max.)	7" (Max.)	
Rewind Speed		Auto mode: 14 IPS (max) Fixed mode: Coreless 5.4 IPS, 1 inch Roll 6.3 IPS		
Label Roll		8" (Max.)	6" (Max.)	
Core Roll		Coreless, 1" (25.2~25.6mm), 1.5"x2 (37.4~38.0mm & 40~40.6mm), 3" (76~76.6mm)		
Label Roll Weight		5 Kg		
Rewinding		Label Inside / Outside		
Switches		Rewind		
Motor		Hybrid Motor		
Power		100~240VAC 24W, 24V Adapter		
Core Roll Label Roll Weight Rewinding Switches Motor	Operation Temp	41°F to 104°F(5°C to 40°C)		
	Storage Temp	-4°F to 122°F(-20°C to 60°C)		
Humidity		10-85% (non-condensing RH)		
Size (H*W*D)		303mm*180mm*349mm	303mm*180mm*394mm	
Agency Approvals		CE, FCC Class A		
Weight		5 Kg (11 lb)		
* Specifications are	subject to change witho	ut notice. All company and/or product names a	re trademarks and/or registered trademarks of their respective	owner