



XL-2002

- Two years warranty
- Firmware can be upgraded online
- With CE, FCC certificates
- Support USB, Keyboard, RS-232 interfaces
- Suitable for supermarkets, pharmacies, retail stores
- Powerful performance on decode capability, can read GS1 code



Omnidirectional Barcode Scanner

Light Source	Visible Laser Diode 650nm	Size	L × W × H:100mm × 100mm × 149mm
Scan Pattern	20 lines 5 fields of 4 parallel lines	Weight	314g
Scan speed	1500 scans/s	Material	ABS+PC
Print Contrast	30% @ UPC/EAN 100%	Laser Class	Meet the Grade I National Criteria for Laser Safety
Minimum Resolution	5mil@PCS90%	Voltage	5 Volts
Depth of Field	0-220mm for 0.33mm UPC/EAN100%	Static Current	250mA
Host System Interfaces	USB, RS232, Keyboard Wedge	EMC	CE & FCC DOC compliance
Visual Indicators	Two color LED (blue & red)	Operating Temperature	- 0°C to 45°C
Beeper Operation	Programmable tone & volume	Storage Temperature	- 20°C to 60°C
Cable	Standard 2M straight	shock	Designed to 1.5m drops



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No. 7, Kehui First Street, Science Road, Science City, Guangzhou, China
Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com