

2D Scan Module

XL-3518



- ⊙ Automatic scan sensor
- ⊙ 32Bit CPU, super decoding ability
- ⊙ Plug and play, work with all POS system
- ⊙ Zinc alloy case, small body and waterproof
- ⊙ Both read 1D,2D barcodes on the screen & paper



Model Number	XL-3518	Size	L x W x H: 68mm x 51.9mm x 26.3mm
CPU	CMOS	Weight	287g
Resolution	752× 480 pixels	Material	Zinc alloy
Light Source	LED (625±10 nm) , RED	Voltage	DC 3.3V±10%
Precision	≥5mil	Working Current	270 mA
Depth of Scan Field	Code39: 35mm-205mm (10mil)	Idle Current	7mA
	EAN-13: 50mm-260mm (13mil)	Standby Current	3uA
	PDF417: 50mm-215mm (10mil), 60mm-285mm (15mil)	Power Consumption	<0.9W
	Data Matrix: 50mm-160mm (10mi), 55mm-225mm (15mil)	Operate Temperature	-20° ~ +55°C
Interface	RS232 , USB	Storage Temperature	-40° ~ +80°C
Print Contrast Signal	≥30%	Humidity	5% to 95% (non-condensing)
Indicator	Buzzer, LED	Ambient Illumination	0 ~ 100000Lux
Scan Mode	Manual & Automatic	Certificates	FCC Part 15 Class B/CE EMC Class B, RoHS
Symbols	1D : Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, UCC/EAN-128, Code 93, GS1 Databar, etc		
	2D : PDF417, QR Code(Model 1/2 , micro), Aztec, DataMatrix (ECC200, ECC000, 050, 080, 100, 140), Maxicode, etc		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No. 7, Kehui First Street, Science Road, Science City, Guangzhou, China
Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com