





# **Features**

### **Outstanding Performance.**

Equipped with an outstanding CPU, the HR22 Dorada Bluetooth wireless handheld scanner can effortlessly capture high density, high volume and distorted barcodes printed on paper or displayed on screen.

# **Exceptional Battery Life.**

With a 2200mAh battery, the HR22 Dorada Bluetooth will run a comfortable 12 hours of continuous use. The provided USB cable allows for convenient charging.

# **Reliable Wireless Connection.**

Adopting the latest Bluetooth 5.0 technology, the HR22 Dorada Bluetooth is able to maintain a wireless connection at distances up to 50 meters from the host device.

# **Durable construction.**

The HR22 Dorada Bluetooth has a more than suitable IP42 rating for its key applications and is drop resistant up to 1.5m. Its durable housing guarantees optimal protection so falls from desktops and countertops are no issue.

# Suggested industries

Logistics







#### Performance

Image Sensor	640x480 CMOS
Illumination	White LED
Aiming	Red LED (625nm)
Depth of Field EAN 13 (13mil)	45-260mm
Depth of Field CODE 39 (5mil)	45-115mm
Depth of Field PDF417 (6.67mil)	50-120mm
Depth of Field Data Matrix (10mil)	35-125mm
Depth of Field QR (15mil)	30-170mm
Minimal Print Contrast	20%
Scan Angle Roll	360°
Scan Angle Pitch	±60°
Scan Angle Skew	±60°
Field of View Horizontal	42°
Field of View Vertical	28°
Data Capture	
1D	All major 1D symbologies, including Code 11, Code 128, Code 39, GS1-128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-8, EAN-13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF-14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS).
2D	All major 2D symbologies, including PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec.
Physical	

Dimensions (mm)	145×101×68
Weight	167g
Interfaces	USB
Expected Battery Life	≥12 hours of continuous operation (scan once per 6 seconds)
Expected Charge Time	≤5.5 hours (with power adapter)
Notifications	Beep, LED indicator, vibration.
Input Voltage	5VDC±5%

Newland EMEA HQ

+31 (0) 345 87 00 33 info@newland-id.com newland-id.com Feel free to contact us or a partner near you visit <u>newland-id.com/partners</u> Specifications are subject to change without notice © Newland EMEA 2021, all rights reserved



# HR22 Dorada Bluetooth Technical specifications

### Environmental

Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±15 kV (air discharge), ±8 kV (direct discharge)
Drop	1.5m
IP Rating	IP42
Wireless	
WPAN RADIO	Bluetooth 5.0/2.4G
Wireless Distance (max.)	Bluetooth:≥50m; 2.4G:≥30m
Communication Modes	Synchronous mode, automatic batch mode and manual batch mode
Software	
Configuration Tools	EasySet
Certifications	
Hardware	FCC Part15 Class B, CE EMC Class B, RoHS, IEC62471, BIS
Warranty	
Standard	3 years

#### Newland EMEA HQ

+31 (0) 345 87 00 33 info@newland-id.com newland-id.com Feel free to contact us or a partner near you visit <u>newland-id.com/partners</u> Specifications are subject to change without notice © Newland EMEA 2021, all rights reserved

