


TP80BE 3" Thermal Receipt Printer

- Quality and Cost-Effective
- Top Paper Loading
- Efficient and Stable Printing
- Easy to Maintenance
- Provide Windows, Linux, POSReady, OPOS Driver
- 80mm Width Paper



Specification

Item		Parameter
Printing	Printing Method	Direct thermal line printing
	Resolution	Default 203 dpi, 180 dpi can be emulated
	Printing Width	72mm(576dots)
	Printing Speed	Max. 230mm/s
	Printing Density	Adjustable from degree 1 to degree 4
	Printing Direction	Vertical and horizontal
Interface	Default	Built-in USB, RS232, LAN
	Optional	N/A
Auto cutter		Partial Cut
Page mode		YES
Memory	RAM	2MB
	Flash	4MB
Character set	Font	Font A:12*24 Font B:9*17 CHN: 24*24
	Number of Columns	48/64
	Alphanumeric	95
	Code page	32
Graphics		Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max. 256K for total)
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code
Detection	Sensor	Paper out, Cover Open

Power supply	Input	AC100V-240V 50-60HZ
	Output	DC 24V±5%, 2.5A,
Paper	Paper Loading	Front loading, Up loading, Easy loading
	Paper Type	Standard thermal paper
	Paper Width	79.5±0.5mm
	Paper Thickness	0.056~0.13mm
	Paper Roll Diameter	83mm Max.
Condition	Operating	0~45°C/10~85%RH
	Storage	-20~60°C/10~90%RH
Reliability	TPH Life	150km
	Cutter Life	1,500,000 times
	Motor Life	360,000 hours
Packing Information	Accessories	
	Power adaptor, RS232 cables, CD, Quick Guide, paper roll	
Emulation		ESC/POS
Driver		Windows(Win10/POSReady/Win8/Win7/Vista/XP/2000), Linux , OPOS
Certifications		CE/CCC
Eco Features		Paper saving mode, Energy Star qualified

