

HM-E300 3" Mobile Receipt Printer

Ultra light, compact and portable
Rugged design passed 1.5m drop test
Bluetooth 3.0/BLE Dual Mode
Multiple wireless interfaces, support iOS, Android, WinCE
USB charging at your convenience
Long-lasting battery life (5 days stand-by)
Support various of 1D & 2D barcode printing
OLED display
MSR for option



Rugged Design



Easy Wireless Connection



OLED Screen

Specification

Item	Parameter	
Printing	Printing Method	Direct Thermal Line Printing
	Resolution	203dpi (8dots/mm)
	Printing Speed	Max. 90mm/s
	Printing Width	72mm
	Interface	USB, Bluetooth
Power Saving	Sleep Mode	YES
Memory	RAM	32Mb
	Flash	64Mb
Resident Fonts	Font	FONT A 12X24; FONT B 8X16; CHN 24X24; 16X16;
	Alphanumeric	95
	Codepage	48
Barcode	1D	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Graphics		Support bitmap printing with different density and user defined bitmap printing
Detection	Sensors	Paper out/Black mark/Gap label sensor, Cover open switch
LED indicator	Power Indicator	Green
	Error Indicator	Red

Power	Input	AC 100 -240V
	Output	DC 5V/1A
	Battery	2300mAh/7.4V rechargeable Li-ion battery
Paper	Paper Type	Continuous paper, black mark paper, linerless label, gap label
	Paper Width	80mm
	Paper Thickness	0.053~0.1mm
	Paper Roller Diameter	≤50mm
	Paper Loading	Easy paper loading
Physical Characteristics	Working Condition	-5°C~50°C, 25%~85%RH
	Storage Condition	-30°C~60°C, 5%~95%RH
	Dimension	138.8(L)*106.3(W)*61.2(H)mm
	Weight	475.8g (Without paper roll)
Options & Accessories		USB Cable, Belt Clip, Power Adapter, Paper Roll, Quick Start Guide, CD
Software	Emulation	ESC/POS
	Driver	Windows
	SDK	WinCE, Win Mobile, Android, iOS

