

TP585 Desk Thermal Receipt Printer

- Cubic and fashionable design
- Dual mode Bluetooth 4.0 optional
- Patent cutter technology, Cutter jam auto-elimination
- Error Reprinting Function



Specification

Item		Parameter
Print Specifications	Print Method	Direct Thermal
	Resolution	203dpi
	Print Speed	100mm/s (Max.)
	Print Width	48mm
	Command	ESC/POS
	Page Mode	Support
	Paper Feeding Direction	forward
Paper Specifications	Type	Thermal receipt paper
	Width	58mm
	Thickness	50~80µm
	Maximum Outer Diameter of Paper Roll	60mm
Characters and Barcode	Characters	Simplified Chinese/Traditional Chinese/Korean/Japanese, 47 codepages
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Sensor		Out-of-paper detection, cover opening detection, over temperature detection, over voltage detection
Communication Interface	Standard	B-type USB, 24V cash drawer
	Optional	Dual-mode Bluetooth、serial interface

Cutter	Type	Slide-type dual cutters
	Cutting Method	Partial cut
Memory	Solution for cutter jam	Auto cutter retreat with opening cover
	RAM	2MB
Electrical Parameters	Flash	4MB
	Input	AC 100~240V, 50/60Hz
Reliability	Output	DC 12V, 2A
	TPH Lifetime	50KM
Environmental Requirements	Cutter Lifetime	1 million
		Operation: 0 to 40℃@ humidity 20% to 85% non-condensingStorage:-20 to 60℃@ humidity 5% to 95% non-condensing
Dimension (L×W× H, mm)		110mmX106mmX114mm
Safety Standard		CCC、CE

