

supoin

SK2201

Durable 1D-code Scanner

The SK2201 1D barcode scanner is one of our handheld equipment that may read various 1D barcodes and on-screen 1D payments, suitable for RS-232, USB, PS2, virtual COM and other PC interfaces, The development package and drivers are provided for free.

Applicable scope: WeChat, Alipay and other mobile payment, retail, tobacco, mobile communication and medical industry.



Characteristics



Excellent Identification Ability :

High-quality 1D engine Accurate reading performance, may also scan all 1D codes on screen.



Sensitive And Responsive Performance :

Manual trigger, continuous scanning with quick and automatic induction system.



Long Service Life :

30 million times service life of button pressing, low power consumption.



High Quality Wires :

Using high quality wires inside and inflaming retarding materials with the international standard, recyclable and practical shell to protect the device properly.



Convenient And Comfortable Handle :

Fashionable and ergonomic design with comfortable handle, convenient for the user for long working hours.



Industrial Grade :

IP54 industrial grade, solid and light can bear drops from a height of 3m on ground impact.

Partners

Microsoft

QUALCOMM

Honeywell

T · · Systems

IN·GRAM

swisslog

SK2201 Specifications

Performance Parameter

Image Sensor	Linear image
Light source	Visible light (610-640nm) (read screen 1D code)
Decoding capabilities	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1, Databar, Code 39, Code 11, MSI-Plessey, Plessey and all internationally general 1D bar codes and screen payment code.
Scanning speed	350 times/s
Angle	±30°, ±60°, ±60°Roll, Pitch, Skew
Resolution	4mil and above
Printing contrast	Minimum 20%
Interface	USB, virtual serial port

Physical Parameters

Overall dimension	LXWXH (110X70X153mm);
Weight	118g
Material	ABS+PC (environment-friendly material)

Environmental Parameters

Operating °C	-20° to 55°C
Storage °C	-40° to 60°C
Luminance of environment	0 Lux – 100,000 Lux
Shock	Falling resistance for 3 meters
IP grade	IP54 grade

Certificates

CCC, RoHS, IP54 grade, CE, FCC and ISO9001



RoHS

Accessories

Optional accessories



The final interpretation of this product is owned by Shenzhen Supoin Technology Corp.

Supoin Technology Corp.

Floor 26, Yinglong Development Center, 6025 Shennan Road,
Futian District, Shenzhen, China

For more information please visit:

www.supoin.net

International hotline:

86-755-82178516

E-mail:

sales@supoin.com



supoin